

Bolt and Chain 2015

ENTRIES

1. **NO ALCOHOL PERMITTED.** STATE LAW ALSO PROHIBITS THE CONSUMPTION OF ALCOHOLIC BEVERAGES WHILE OPERATING A VEHICLE. THEREFORE, NO DRIVER UNDER THE INFLUENCE OF ALCOHOL OR DRUGS WILL BE ALLOWED TO PARTICIPATE OR ENTER THE EXHIBITION AREA. JUDGES MAY DISQUALIFY A DRIVER IF HE/SHE IS CONSIDERED UNFIT TO DRIVE. LAW ENFORCEMENT WILL BE NOTIFIED OF VIOLATIONS.
2. Orderly conduct is required of all drivers and pit persons. If not, any driver and or people affiliated with that car will be evicted without any refunds or prize money. Misconduct may result in being banned from present and/ or future participation. Any driver or crewmember not complying with any one of the rules will be immediately disqualified. Crew members are the responsibility of the driver..
3. All cars must be in the pit one hour prior to start.
4. All cars will be inspected and passed before allowing participation.
5. No ambulances, hearses, trucks, vans, Chrysler Imperials or convertibles will be entered. No diesel motors.
6. NO one allowed in pit area without a pit pass!
7. All cars not removed the day after demo, become the property of the Inter State Fair.
8. Entry fee refunds will be made only on cars that do not pass inspection. (NO SHOW NO REFUND.)
9. Entrants and pit crews are expected to wear pit pass at all times.
10. Sub-frames or uni-body are considered frames

CAR PREP

- A) All glass, plastic, fiberglass, chrome moldings, molding clips, door handles (inside and out) and pot metal **MUST** be removed prior to arrival at facility. No broken window in doors.
- B) No flammable materials such as carpets, upholstery or headliners can be left in the car.
- C) Cars **MUST** be clean and free of loose objects inside the entire vehicle.
- D) Insulation blankets under the hood and in trunk **MUST** be removed.
- E) Wheel weights must be removed.
- F) Fuel tanks must be removed.

BUMPERS

- A) Bumpers may be changed to any factory car bumper using stock brackets. Can place one piece of pipe or tubing inside bumper **NO** thicker than 1/4 inch **MUST** be able to see through. **NO MANUFACTURED BUMPERS**
- A) May be compressed and welded, brackets can be welded to frame **NO REPLACING OF BRACKETS TO FRAME OR RELOCATING!**
- B) May weld a 6" piece of chain on stock bumpers to keep from coming off.

DOORS

- A) Drivers' doors must be solid welded shut. If door comes open driver will be disqualified from the heat. This door can be welded solid.
- B) DRIVER'S DOOR MUST BE PADDED ON THE INSIDE!
- C) REINFORCEMENT MUST BE ADDED ON THE DRIVER'S DOOR, limited to 6" past edge of door, and MAY NOT protrude from car more than 2". This door can be welded solid. No grader blades.
- D) Passenger doors may be chained (max of 3/8 in.) or welded with TWO, 1" strap 3" long. No wood, or extra reinforcing allowed in passenger doors.

TRUNK LID

- A) Trunk lid may **NOT** be welded. (Must be able to be open for inspection) and then may be chained with two chains no larger than 3/8".
- B) May remove trunk lid and lay down in trunk. may be held down with 2 bolts no bigger than 3/4 inch.
- C) Trunk lid can be bent, but must be in stock location(NO WELDING IN PLACE)

HOOD

- A) Hood can be chained down with a maximum of four 3/8" chains, or six bolts (TWO BOLTS CAN GO TO FRAME), or four 9 wire points.
 - A1) MUST BE ABLE TO OPEN HOOD.
- B) Front chain, wire or 1/4" cable may go around bumper and around frame.

FINDERS

- A) Maybe trimmed or folded. NO BOLTS OR WELDS

FUEL

- A) Fuel tanks must be in the rear seat compartment and fastened securely
- B) Fuel tank size is a maximum 10 gallons. (Metal or plastic boat gas tanks work very well.)
- C) For driver safety, fuel tank must to be covered.
- D) Fuel line must be connected with secure fittings. (Two clamps for every connector.)

BATTERIES

- A) Batteries must be moved to front seat compartment and fastened securely.
- B) Batteries must be covered for driver's safety. Two batteries maximum or one car battery may be used.

DRIVE TRAIN

- A) Air cleaners must be left in place. All carburetors will have one.
- B) Radiator must be left in place and no other water supply may be used.
- C) For safety leave firewalls intact and heater core covered.

DRIVER COMPARTMENT

- A) **A box around the driver and batteries is required.** A safety bar is required to be welded behind driver's seat, running parallel to the floor from driver's side to passenger's side of the car. You may have a bar that extends across the dash and also have one that runs from dash bar to the seat bar on the passenger side. These bars may not exceed 4" diameter and can be welded to frame.
- B) May reinforce the drivers' seat with chain.
- C) Must have at least three front window bars in front of the driver.
- D) **Must have a fire extinguisher in car.**

SUSPENSION FRAME

- A) No shock welding. Car suspension must have movement in the front and back.
- B) Must have stock springs no wider than 3" with no helper springs.
- C) **No Leaf Conversions!**
- D) Rubber mounts must be in place on frame.
- E) All frame holes must be open. No metal, wood and or concrete allowed in frame.
- F) **No Frame Lacing or Welding. No Frame Pinning!**
- G) May tilt frame (cold Tilt) NO EXTRA PLATES!
- H) **Pre ran cars may weld TWO 3" plates per frame rail, 1/4 inch thick (IF NEEDED)**

PAINT

- A) PAINT CAR NUMBER ON ROOF IN LARGE NUMBERS.
- B) PAINT DRIVERS NAME ON ROOF IN LARGE LETTERS.

TIRES

- A) May have a modified rim, to allow for 16" tires, no more than 1/4" material.
- B) May run any tire you want, as long as it goes under car.

GOLDEN RULE

- A) **If you decide to push these rules you will be advanced into the normal derby.**
- B) **If it doesn't say you canDON'T**

CLAIM RULE

1. All cars (In final) of the Weekend Warrior are allowed to be claimed for \$500 plus two drivers swap cars. (both get to remove their stuff)
2. Cars can only be claimed by other drivers in the Weekend Warrior heat!!!
3. Only top 5 cars can be claimed, by any top 5 driver (Weekend Warrior).
4. All claims must be turned into the (HEAD) flagman immediately following the heat.
5. If your car is claimed you must forfeit your car or risk losing your placing in the event. If someone does don't forfeit their car they lose their winnings and everyone else moves up in placing. (If winner don't forfeit car to claim, then the second place car gets the 1st place winnings and etc.)
6. If your car is claimed you are allowed to remove the gas tank, batteries, headers, REAR tires, and driver's seat. Everything else must stay. **ALL MONEY (\$500) GOES TO THE CLAIMED DRIVER AND HE GETS THE OTHER DRIVERS CAR!!**

DRIVER RULES

1. All drivers must have a valid drivers license and be at least 18 years of age. If not 18 years old, driver must have written permission and notarization from Parents or Guardians. Each driver and mechanic must sign a waiver releasing Inter State Fair from liability.
2. Helmets with face shields or helmets with goggles must be worn. (Safety glasses not considered as goggles or shield.) Long sleeved shirt or fire suit is required. **NO SHORTS!**
3. Seat belts must be worn. Shoulder harnesses are recommended.
4. Driver's door hits and team driving will be decided by the judges.
5. Any door or hood coming open during race, that car will be removed from that heat.
6. Drivers must be present at drivers meeting held 30 min. before the show. Roll will be called.
7. Driver must make a hit at least every one minutes during race.
8. When call goes out for cars to be in place, drivers shall be in place and ready or will be disqualified from that heat.
9. Two wheels going over poles or boundary line car will be disqualified!
10. Cars catching on fire 2 times in one heat will be disqualified from the heat.
11. **ALL CARS WILL STOP IMMEDIATELY WHEN FLAGGED. (FOR FIRES, ETC.)**
12. All rulings by the Official Judge will be final.
13. Drivers must stay in car for safety reasons until the heat is over, except in case of fire.
14. **ALL CARS ARE SUBJECT TO REINSPECTION AT ANY TIME.**
15. Judges may disqualify a car if it is deemed unsafe.
16. Drivers **MUST** accompany their car to the inspection. **NO EXCEPTIONS.**
17. Hood must be open for all inspections.
18. Roll overs will be disqualified!!!

Any Questions Contact:

Joe Hibbert 620- 255-1531

COMPACT DEMO RULES

ENTRIES

1. **NO ALCOHOL PERMITTED.** STATE LAW ALSO PROHIBITS THE CONSUMPTION OF ALCOHOLIC BEVERAGES WHILE OPERATING A VEHICLE. THEREFORE, NO DRIVER UNDER THE INFLUENCE OF ALCOHOL OR DRUGS WILL BE ALLOWED TO PARTICIPATE OR ENTER THE EXHIBITION AREA. JUDGES MAY DISQUALIFY A DRIVER IF HE/SHE IS CONSIDERED UNFIT TO DRIVE. LAW ENFORCEMENT WILL BE NOTIFIED OF VIOLATIONS.
2. Orderly conduct is required of all drivers and pit persons. If not, any driver and or people affiliated with that car will be evicted without any refunds or prize money. Misconduct may result in being banned from present and/or future participation. Any driver or crewmember not complying with any one of the rules will be immediately disqualified. Crewmembers are the responsibility of the driver.
3. All cars must be in the pit 1 hour prior to show.
4. All cars will be inspected and passed before allowing participation.
5. NO one allowed in pit area without a pit pass!
6. All cars not removed the day after demo, become the property of the Inter State Fair.
7. Entrants and pit crews are expected to wear pit pass at all times.
8. Sub-frames or uni-body are considered frames in all parts of these rules.

CAR PREP

- A) All glass, plastic, fiberglass, chrome moldings, molding clips, door handles (inside and out) and pot metal **MUST** be removed prior to arrival at facility. No broken window in doors.
- B) No flammable materials such as carpets, upholstery or headliners can be left in the car.
- C) Cars **MUST** be clean and free of loose objects inside the entire vehicle.
- D) Insulation blankets under the hood and in trunk **MUST** be removed.
- E) Wheel weights must be removed.
- F) Fuel tanks must be removed.
- G) 108" wheel base or less.
- H) No full size conversions.
- I) May run Trucks

BUMPERS

- A) Bumpers may be changed to any factory car bumper.
- B) Bumper can be welded together cut and welded together.
- C) You can hard nose (no extra material).
- D) You may stuff bumpers or build a bumper (**MUST APPEAR TO BE STOCK**) METAL ONLY!
- E) Can relocate in trunk only! IF you don't run a rear bumper the bumper shocks **MUST** be removed!!!!
- F) May trim bumpers. When trimming off bumpers please keep people's safety in mind.
- G) Shocks can be collapsed and welded. **NO EXTRA MATERIAL.**
- H) If you extend shocks, they must have a ¼ hole for inspection! **NO EXCEPTIONS!** No homemade shock mount!
- I) May have 2 chains or 2 wraps of #9 wire, or two straps 2" long or two cables ¼" thick. **NOT MORE THAN ONE** that can go around bumper and around frame. (Front and back) Maximum two wraps. No crossing allowed!
- J) May weld rear bumper to trunk lid, may use 2" strap.

FRAMES

- A) May weld frame from transmission cross over forward top and bottom. ALL WELDS NO WIDER THAN $\frac{3}{4}$ inch!!!
- B) May weld 12 more inches long and $\frac{3}{4}$ inch wide, more top or bottom else where on both sides of frame.
- C) No metal, wood, foreign material and or concrete allowed in frame.
- D) No frame to body welds!! NEED TO KEEP $\frac{1}{4}$ GAP!
- E) No Frame Pinning! No Frame Lacing!!
- F) All frame holes must be open, no welding shut or washers added!! YOU PICK THE CARS WE DON'T!
- G) May tie frame rails together by rear end with chain or 2 wraps of #9 wire (no further forward than hump)
- H) Previous ran cars with broken or cracked frames may be re-welded where broken, but no farther than 2" (length) farther than crack in frame on either side of crack, no wider than $\frac{3}{4}$ inch. Do not add filler material on weld and only one bead for cracks!! IF METAL IS ADDED THEN IT WILL COUT AS ONE OF YOUR PLATES.
- I) May pre-plate frames with plates, you may only use 6 total plates, 6 inches x 4 inches x $\frac{1}{4}$ inch.
- J) No frame painting or undercoating or rhino lining to hide welds. WILL NOT BE INSPECTED FOR SHOW!!!!

SUSPENSION

- A) Rear coil springs can be changed, but must fit in stock location.
- B) May chain differential to the floor or humps. (3/8 chain max.) or 2 wraps of #9 wire per side. NO PINNING!!
- C) May reinforce A arms, must look like an A arm!! May weld or bolt to frame. Or four 1" straps per A-arm
- D) May reinforce steering arms (1/4 inch material) or 2 inch angle iron.
- E) May run modified rims no larger than $\frac{1}{4}$ inch material. May modify rim, to allow for 16" tires.
- F) No tire rule, but they must fit the car. (NO Monster Tires!!!)
- G) 5" x 5" washer max for body bolt replacing top and bottom.
- H) No shock altering, over springs etc.

BODY

- A) Doors may be welded with no more than a 3" strap solid. No wood, no foreign material or extra reinforcing allowed inside passenger doors.
- A1) Driver's doors must be welded shut. If door comes open driver will be disqualified from the heat. REINFORCEMENT MUST BE ADDED ON THE DRIVER'S DOOR, limited to 6" past edge of door, and MAY NOT protrude from car more than 2". This door can be welded solid.
- A2) Only True grader blades allowed. No V blades.
- A3) DRIVER'S DOOR MUST HAVE ALL LATCHES OR SHARP OBJECTS REMOVED!!! HIGHLY RECOMMEND PAD ON THE INSIDE!
- A4) Torn sheet metal in doors can be patched with sheet metal only 2" lap, for safety reasons only!! 1/8 sheet metal only!
- A5) No filling in headlights with extra metal.

TRUNKS

B) Trunks may be welded solid or with a 3inch strap not both (NO ANGLE IRON). 1/4" thick.

B1) Trunk lids MUST have a 6 inch inspection hole. Station wagons must have rear deck plates removed!!

B2) Minimal pre-bending of body is allowed, no full rear end wedges before car is ran. A pre-ran car may smash the trunk down for visibility reasons only.

B3) Trunk may have two 1 inch all threads TOTAL and can be through the frame . A maximum 6"x6"x1/4" washer on trunk bolts

B4) Trunk may be tucked into rear tail light cross brace, bend may start 10" back from end of trunk

HOODS

C) 100% of Hood must be removable. (one hood only)

C1) Hole must be cut in hood, large enough for fire extinguisher use.

C2) A maximum of 8 bolts or all thread maybe used on the hood. Only four all threads TOTAL can go to frame.

C3) The bolts shall be no more than 1" maximum. A maximum 6"X 6" washer on hood bolts.

C4) You can weld together or bolt hood together with no more than 30 3/8 bolts and 1" washers.

C5) You are allowed to run two straps 2 inch wide 1/4 inch thick from core support to bumper or 2 wraps of # 9 wire or 1/4" cable CHOOSE ONLY ONE!! No other reinforcing or added material to core support.

D) May weld all body seems under the hood (fenders to fender wells ect.)

D1) You can weld fender to core support

E) NO inside seems may be welded in the drivers area or trunk !

F) May have 8 bolts per fender 3/8 inch max or weld.

G) For safety try to leave firewalls intact and heater core covered. Driver's floor board must be in place. May cut for motor mod, but needs to have some cover!

H) Must have at least three front window bars in front of the driver can not be located directly behind distributor protector. May have two bars in back window NO larger 2 inch angle iron or pipe, (not welded to halo bar or 6" past speaker lid or back window pillar).

I) All windows may have one 9-wire (2 wraps) or 1/4 cable(with one turn buckle) in one place not both!

DRIVERS COMPARTMENT

A) A box (cage) around the driver and batteries is required. You are required to have at least a driver's door bar, a bar from door post to door post, a dash bar and a bar from the dash bar to the door post bar on the passenger side.

A1) The 4 vertical bars ONLY can be welded to the frame or bolted to frame no more than 3 places per frame rail.

A2) You are allowed to run a vertical bar from the door to door bar of X-brace behind the seat straight up and connect to two together on top of the roof (roll bar). Located NO futher back than the middle of the back door behind driver!!

A3) No kickers from cage to frame with a distributor protector.. If you don't run a protector you may have two kickers (one)per side 1/4 angle iron 6" long.

A4) The only part of the cage allowed outside the car is the driver's door and the bar across the roof.

A5) MUST HAVE INSIDE DOOR BAR FROM DASH TO SEAT BAR, TO PROTECT THE BATTERIES.

FUEL

B) Fuel tanks must be in the rear seat compartment and fastened securely.

B1) Fuel tank size is a maximum 10 gallons (Metal or plastic boat gas tanks work very well.) Need cover (metal or inertube)

B2) Fuel line must be connected with secure fittings. (Two clamps for every connector.)

B3) Fuel line must be protected when passing through sheet metal.

B4) No Alcohol!!

B5) Fuel protectors CAN NOT be fastened to the back fire wall or have floor kickers!!

BATTERIES

C) Batteries must be moved to front seat compartment and fastened securely

C1) Batteries must be covered for driver's safety.

C2) Two batteries maximum or one cat battery may be used.

DRIVE TRAIN

A) Air cleaners must be left in place. All carburetors will have one.

B) Radiator must be left in place and no other water supply may be used.

C) May run 1/4" expanded metal in front of radiator, welded in 4 (1") spots. Cannot overlap metal by more than one 1" of core support. No overlapping or welding to bumper.

D) May run radiator tank with pop off valve in place of a stock radiator.(Must Not Be used as enforcement)

E) You may run transmission coolers. They must be securely fastened.

F) No water engine cooled coolers

G) May run distributor protectors

H) May run engine cradles but they must be attached to the engine sub frame , transmission cross over and one other place.

I) Motor mounts can be welded down and not out.

J) Radiator support can be in a U shape under frame but not straight frame rail to rail solid. Radiator support must support not reinforce, overlapping will be counted as plates!

PAINT

A) PAINT CAR NUMBER ON ROOF IN LARGE NUMBERS. Roof signs are recommended.

B) PAINT DRIVERS NAME ON ROOF IN LARGE LETTERS.

DRIVER RULES

1. All drivers must have a valid driver's license and be at least 18 years of age. If not 18 years old, driver must have written permission and notarization from Parents or Guardians, Each driver and mechanic must sign a waiver releasing Inter State Fair from liability.

2. Helmets with face shields or helmets with goggles must be worn. (Safety glasses not considered as goggles or shield.) Long sleeved shirt or fire suit is required. NO SHORTS!

3. Seat belts must be worn. Shoulder harnesses are recommended.

4. Driver's door hits and team driving will be decided by the judges.

5. Any door or hood coming open during race, that car will be removed from that heat.

6. Drivers must be present at drivers meeting held 30 min. before the show. Roll will be called.

7. Driver must make a hit at least every one minutes during race.

8. When call goes out for cars to be in place, drivers shall be in place and ready or will be disqualified from that heat.

9. Two wheels going over poles or boundary line car will be disqualified!

10. Cars catching on fire 2 times in one heat will be disqualified from the heat.

11. ALL CARS WILL STOP IMMEDIATELY WHEN FLAGGED. (FOR FIRES, ETC.) OR THEY WILL BE BLACK FLAGGED.

12. *All rulings by the Official Judge will be final.*
13. *Drivers must stay in car for safety reasons until the heat is over, except in case of fire.*
14. *ALL CARS ARE SUBJECT TO REINSPECTION AT ANY TIME.*
15. *Judges may disqualify a car if it is deemed unsafe.*
16. *Drivers MUST accompany their car to the inspection. NO EXCEPTIONS.*
17. *Hood must be open for all inspections.*
18. *Roll overs are disqualified!!!*
- 19) *Must have Fire extinguisher inside*

Any Questions Contact:

Joe Hibbert 620- 255-1531

Modified Weld 2015

ENTRIES

1. **NO ALCOHOL PERMITTED.** STATE LAW ALSO PROHIBITS THE CONSUMPTION OF ALCOHOLIC BEVERAGES WHILE OPERATING A VEHICLE. THEREFORE, NO DRIVER UNDER THE INFLUENCE OF ALCOHOL OR DRUGS WILL BE ALLOWED TO PARTICIPATE OR ENTER THE EXHIBITION AREA. JUDGES MAY DISQUALIFY A DRIVER IF HE/SHE IS CONSIDERED UNFIT TO DRIVE. LAW ENFORCEMENT WILL BE NOTIFIED OF VIOLATIONS.
2. Orderly conduct is required of all drivers and pit persons. If not, any driver and or people affiliated with that car will be evicted without any refunds or prize money. Misconduct may result in being banned from present and/ or future participation. Any driver or crewmember not complying with any one of the rules will be immediately disqualified. Crewmembers are the responsibility of the driver.
3. All cars must be in the pit one hour prior to show
4. All cars will be inspected and passed before allowing participation
5. NO one allowed in pit area without a pit pass!
6. All cars not removed the day after demo, become the property of the Inter State Fair.
7. Entrants and pit crews are expected to wear pit pass at all times.
8. Sub-frames or uni-body are considered frames in all parts of these rules.

CAR PREP

- A) **All glass, plastic, fiberglass, chrome moldings, molding clips, door handles (inside and out) and pot metal MUST be removed prior to arrival at facility. No broken window in doors.**
- B) **No flammable materials such as carpets, upholstery or headliners can be left in the car.**
- C) **Cars MUST be clean and free of loose objects inside the entire vehicle.**
- D) **Insulation blankets under the hood and in trunk MUST be removed.**
- E) **Wheel weights must be removed.**
- F) **Fuel tanks must be removed.**

BUMPERS

- A) **Bumpers may be changed to any factory car bumper.**
- B) **Bumper can be welded together cut and welded together**
- C) **You can hard nose (no extra material).**
- D) **You may stuff bumpers or build a bumper (MUST APPEAR TO BE STOCK) METAL ONLY)**
If you build pointy MUST be 11 inches deep MAX, with a 3 inch blunt point!!!
- E) **Can relocate in trunk only! IF you don't run a rear bumper the bumper shocks MUST be removed!!!!**

- F) May trim bumpers. When trimming off bumpers please keep people's safety in mind.**
- G) Shocks can be collapsed and welded NO EXTRA MATERIAL.**
- H) If you extend shocks. They must have a 1/4 hole for inspection! NO EXCEPTIONS! No homemade shock mount!**
- I) Or Instead of using bumper brackets you are allowed to use 1- 4" wide x 3/8" thick strap extending from your bumper down one side of the frame and cannot extend any further back than the very front most part of your top-front a-arm bracket.**
- J) May have 2 Chains or 2 wraps of #9 wire, or two straps 2" long or two cables 1/4" thick . NOT MORE THAN ONE that can go around bumper and around frame. (Front and back) Maximum two wraps. No crossing allowed!**
- K) May weld rear bumper to trunk lid, may use 2" strap.**

FRAMES

- A) May weld frame from transmission cross over forward top and bottom ALL WELDS NO WIDER THAN 3/4 inch!!!**
- B) May weld 12 more inches long and 3/4 inch wide, more top or bottom elsewhere on both sides of frame .**
- C) K frames must leave one ear up Y frame you can close gap with a 1/4" plate but must have 1/4 hole for scope**
 - C1) May remove pucks in K frame subs, but must be bolted with no more than 1" ready rod (no space required)**
- D) Suicides must have a 1" hole in front frame rails between fire wall and A arms for bore scopes.**
- E) NO Imperials. No Imperial Subs, Stubs or Full frames under any cars!!**
- F) No metal, wood , foreign material and or concrete allowed in frame.**
- G) No frame to body welds!! NEED TO KEEP 1/4 GAP!**
- H) No Frame Pinning! No Frame Lacing!!**
- I) All frame holes must be open, No welding shut or washers added!! YOU PICK THE CARS WE DON'T!**
- J) May tie frame rails together by rear end with chain or 2 raps of #9 wire (no further forward than hump)**
- K) Previous ran cars with broken or cracked frames may be re-welded where broken, but no farther than 2" (length) farther than crack in frame on either side of crack, no wider than 3/4**

inch. Do not add filler material on weld and only one bead for cracks!! IF METAL IS ADDED THEN IT WILL COUNT AS ONE OF YOUR PLATES.

- L) May pre-plate frames with plates, you may only use 6 total plates, 6 inch x 4 inches x 1/4 inch.**
- M) With Rule (L) May have two rear hump plates 18 inches long if you choose, must be in rear humps must follow cure of frame NOT TRANSFERABLE**
- N) May tilt frames but you may only use 12 inches of weld per side. [This is your extra 12 inch of weld]**
- O) No frame painting or undercoating or rhino lining to hide welds. WILL NOT BE INSPECTED FOR SHOW!!!!**
- P) All holes must be open on Crow Vic crush boxes.**
- Q) Washers on crush box MUST be separated**

SUSPENSION

- A) 80- newer may covert coil to leaf spring NO HUMP PLATES**
- B) May run a floater rear end No larger than 3/4 ton rear ends allowed.**
- C) Rear coil springs can be changed, but must fit in stock location.**
- D) No more than 9 leafs under leaf cars!!! May be taped or four keeps per pack, but have a place to count leaves, no more than 1/4 inch x 2 inch metal for the leaf strengtheners. Must have springs no wider than 3" Total stack height must not exceed 3.5"**
- E) May chain rear differential to the floor or humps. (3/8 chain max.) or 2 wraps of # 9 wire per side NO PINNING!!**
- F) May reinforce A arms, must look like an A arm!! May weld or Bolt to frame. Or 4 1" strap per A-arm**
- G) May reinforce steering arms (1/4 inch material) or 2 inch angle iron.**
- H) May run modified rims no larger than 1/4 inch material. May modified rim, to allow for 16" tires.**
- I) No tire rule, but they must fit the car (NO Monster Tires!!!)**
- J) You may convert a watts link rear end to a standard G M standard in the following way; use a ford of the same size and thickness. No positioning of brackets to strengthen front down leg of rear hump. You may cut coil spring tray of an older tray and weld in newer Ford. Weld one pass 1/4" max no stronger than stock.**
- K) 2003 and Newer Fords-- You can change steering components, but no welding to frame, bolt in no modifications. May run gusset outside crush box 2"x 6" x1/4" in stock location.**
- L) 80-new allowed to tilt. You can cut frame, pull down re- weld. You can use a 2" pipe for front spacer and can be welded to frame.**
- M) 5" x 5" washer max for body bolt replacing top and bottom.**

- O) No shock altering, over springs etc.
- P) May have spring spaces no larger than 1"
- Q) May stuff or enforce rear control arms.
- R) Front clips can ONLY be changed with same kind Ford to Ford etc.

BODY

- A) Doors may be welded with no more than a 3" strap solid. No wood, no foreign material or extra reinforcing allowed inside passenger doors.
- A1) Drivers' doors must be welded shut. If door comes open driver will be disqualified from the heat. **REINFORCEMENT MUST BE ADDED ON THE DRIVER'S DOOR**, limited to 6" past edge of door, and **MAY NOT** protrude from car more than 2". This door can be welded solid.
- A2) Only True grader blades allowed. No V blades.
- A3) **DRIVER'S DOOR MUST HAVE ALL LATCHES OR SHARP OBJECTS REMOVED!!! HIGHLY RECOMEND PAD ON THE INSIDE!**
- A4) Torn sheet metal in doors can be patched with sheet metal only 2" lap, for safety reasons only!! 1/8 sheet metal only!
- A5) No filling in headlights with extra metal.

TRUNKS

- B) Trunks may be welded solid or with a 3inch strap not both (NO ANGLE IRON). 1/4" thick.
- B1) Trunk lids **MUST** have a 6 inch inspection hole. Station wagons must have rear deck plates removed!!
- B2) Minimal pre-bending of body is allowed, no full rear end wedges before car is ran. A pre-ran car may smash the trunk down for visibility reasons only.
- B3) Trunk may have two 1 inch all threads **TOTAL** and can be through the frame. A maximum 6"x6"x1/4" washer on trunk bolts
- B4) Trunk may be tucked into rear tail light cross brace; bend may start 10" back from end of trunk.

HOODS

- C) 100% of Hood must be removable. (one hood only)
- C1) Hole must be cut in hood, large enough for fire extinguisher use.
- C2) A maximum of 8 bolts or all thread maybe used on the hood. Only four all threads **TOTAL** can go to frame.
- C3) The bolts shall be no more than 1" maximum. A maximum 6"X 6" washer on hood bolts.

- C4) You can weld together or bolt hood together with no more than 30 3/8 bolts and 1" washers.
- C5) You are allowed to run two straps 2 inch wide 1/4 inch thick from core support to bumper or 2 wraps of # 9 wire or 1/4" cable **CHOOSE ONLY ONE!!** No other reinforcing or added material to core support.
- D) May weld all body seems under the hood (fenders to fender wells etc.)
- D1) You can weld fender to core support.
- E) **NO** inside seems may be welded in the drivers area or trunk!
- F) May have 8 bolts per fender 3/8 inch max or weld.
- G) For safety try to leave firewalls intact and heater core covered. Driver's floor board must be in place. May cut for motor mod, but needs to have some cover!
- H) Must have at least three front window bars in front of the driver cannot be located directly behind distributor protector. May have two bars in back window **NO** larger 2 inch angle iron or pipe, (not welded to halo bar or 6" past speaker lid or back window pillar).
- I) All windows may have one 9-wire (2 wraps) or 1/4 cable(with one turn buckle) in one place not both!

DRIVERS COMPARTMENT

- A) A box (cage) around the driver and batteries is required. You are required to have at least a driver's door bar, a bar from door post to door post, a dash bar and a bar from the dash bar to the door post bar on the passenger side.
- A1) The 4 vertical bars **ONLY** can be welded to the frame or bolted to frame no more than 3 places per frame rail.
- A2) You are allowed to run a vertical bar from the door to door bar of X-brace behind the seat straight up and connect to two together on top of the roof (roll bar). Located **NO** further back than the middle of the back door behind driver!!
- A3) May have two kickers from dash bar to frame with a distributor protector 6" from back of A-Arm. IF your distributor protector is not within 6" of Dash Bar (2" MAX MATERIAL) CAN NOT be a continuous bar from HALO.. If distributor protector is against dash bar "NO KICKERS"!!
- A4) The only part of the cage allowed outside the car is the driver's door and the bar across the roof.
- A5) **MUST HAVE INSIDE DOOR BAR FROM DASH TO SEAT BAR, TO PROTECT THE BATTERIES.**

FUEL

- B) Fuel tanks must be in the rear seat compartment and fastened securely.
- B1) Fuel tank size is a maximum 10 gallons (Metal or plastic boat gas tanks work very well.) Need cover (metal or inner tube)
- B2) Fuel line must be connected with secure fittings. (Two clamps for every connector.)
- B3) Fuel line must be protected when passing through sheet metal.
- B4) No Alcohol!!
- B5) Fuel protectors **CAN NOT** be fastened to the back fire wall or have floor kickers!!

BATTERIES

- C) Batteries must be moved to front seat compartment and fastened securely

- C1) Batteries must be covered for driver's safety.
- C2) Two batteries maximum or one cat battery may be used.

DRIVE TRAIN

- A) Air cleaners must be left in place. All carburetors will have one.
- B) Radiator must be left in place and no other water supply may be used.
- C) May run 1/4" expanded metal in front of radiator, welded in 4 (1") spots. Cannot overlap metal by more than one 1" of core support. No overlapping or welding to bumper.
- D) May run radiator tank with pop off valve in place of a stock radiator.(Must Not Be used as enforcement)
- E) You may run transmission coolers. They must be securely fastened.
- F) No water engine cooled coolers
- G) May run distributor protectors
- H) May run engine cradles but they must be attached to the engine sub frame , transmission cross over and one other place.
- I) Motor mounts can be welded down and not out.
- J) Radiator support can be in a U shape under frame but not strait frame rail to rail solid. Radiator support must support not reinforce; overlapping will be counted as plates!

PAINT

- A) PAINT CAR NUMBER ON ROOF IN LARGE NUMBERS. Roof signs are recommended.
- B) PAINT DRIVERS NAME ON ROOF IN LARGE LETTERS.

DRIVER RULES

1. All drivers must have a valid driver's license and be at least 18 years of age. If not 18 years old, driver must have written permission and notarization from Parents or Guardians, Each driver and mechanic must sign a waiver releasing Inter State Fair from liability.
2. Helmets with face shields or helmets with goggles must be worn. (Safety glasses not considered as goggles or shield.) Long sleeved shirt or fire suit is required. NO SHORTS!
3. Seat belts must be worn. Shoulder harnesses are recommended.
4. Driver's door hits and team driving will be decided by the judges.
5. Any door or hood coming open during race, that car will be removed from that heat.
6. Drivers must be present at driver's meeting held 30 min. before the show. Roll will be called.
7. Driver must make a hit at least every one minutes during race.
8. When call goes out for cars to be in place, drivers shall be in place and ready or will be disqualified from that heat.
9. Two wheels going over poles or boundary line car will be disqualified!
10. Cars catching on fire 2 times in one heat will be disqualified from the heat.
11. ALL CARS WILL STOP IMMEDIATELY WHEN FLAGED. (FOR FIRES, ETC.) OR THEY WILL BE BLACK FLAGED.
12. All rulings by the Official Judge will be final.
13. Drivers must stay in car for safety reasons until the heat is over, except in case of fire.
14. ALL CARS ARE SUBJECT TO REINSPECTION AT ANY TIME.
15. Judges may disqualify a car if it is deemed unsafe.
16. Drivers MUST accompany their car to the inspection. NO EXCEPTIONS.
17. Hood must be open for all inspections.
18. Roll overs are disqualified!!!
- 19) Must have Fire extinguisher inside

Any Questions Contact:

Joe Hibbert 620- 255-1531